

ECOsystem Spaceborne Thermal Radiometer Experiment on Space Station

& ECOSTRESS

Simon J. Hook and the ECOSTRESS Team

Jet Propulsion Laboratory,

California Institute of Technology, Pasadena, CA

With support, encouragement and participation from many!

© 2017 California Institute of Technology. Government sponsorship acknowledged.

SECOSTRESS




ECOsystem Spaceborne Thermal Radiometer Experiment on Space Station


Dr. Simon J. Hook, JPL, Principal Investigator

Science Objectives

- Identify critical thresholds of water use and water stress in key climate-sensitive biomes
- Detect the timing, location, and predictive factors leading to plant water uptake decline and/or cessation over the diurnal cycle
- Measure agricultural water consumptive use over the contiguous United States (CONUS) at spatiotemporal scales applicable to improve drought estimation accuracy



When stomata close, CO2 uptake and evapotranspiration are halted and plants risk starvation, overheating and death.




Water stress is quantified by the Evaporative Stress Index, which relies on evapotranspiration measurements.

ECOSTRESS will provide critical insight into plant-water dynamics and how ecosystems change with climate via high spatiotemporal resolution thermal infrared radiometer measurements of evapotranspiration from the International Space Station (ISS).

SECOSTRESS






Mission

- Class D \$30M cost cap
- 31-months from project start to delivery
- JPL implementation and management
- 69-month project duration (Phase A-F)
- On ISS-JEMS Module
- 12-month Science Operations (Phase E)



The inclined, precessing ISS orbit enables ECOSTRESS to sample the diurnal cycle in critical regions across the globe at spatiotemporal scales missed by current instruments in Sunsynchronous polar and high-altitude geostationary orbits.




Cal Year	2014	2015	2016	2017	2018	2019
KDP		ВС	Acc.		F	
Phase	,	АВ	P C	Ready \	Delivery	F
Milestone	ATP Oct 1	SRR/ PDR MDR	CDR	TRR CoFR PS	ATLO IOC Laur R ORR	ich

Instrument


- Leverages functionally-tested PHyTIR space-ready hardware developed under the NASA Instrument Incubator Program:
 - Spectral resolution: 5 bands in the thermal infrared window (8-12.5 μm) part of the electromagnetic spectrum
 - Noise equivalent delta temperature: ≤ 0.3 K
- Spatial resolution: 38 m x 69 m
- Swath width: 400 km @ 400 km altitude (51°)
- Well understood measurement and algorithms based on prior missions, such as ASTER, MODIS, and Landsat

SECOSTRESS





Push-whisk System



Science Data Products					
L0	Raw data				
L1	Radiometrically corrected Brightness Temperature				
L2	Surface Temperature and Emissivity				
L3	Evapotranspiration				
L4	Water Use Efficiency, Evaporative Stress Index				

Science Team

Principal Investigator Simon Hook, JPL

Co-Investigators

Rick Allen, Univ. of Idaho Martha Anderson, USDA Joshua Fisher, JPL Andrew French, USDA Glynn Hulley, JPL Eric Wood, Princeton Univ.




Christopher Hain, Univ. Maryland














Mission Concept



Radiometer Instrument



ECOSTRESS Payload






Dragon-Trunk Falcon-9 LV




Installation on JEM-EF




Science Data Processing and **Archive**





MOS and Ground and Space Network

MOS and Ground and Space Network



Data Collection







Current Events



- 4/26/17 ETRR
- Ω2/Ω8/17 Fab MMR
- 01/20-21/17 ECOSTRESS One TIM at Marchall
- 01/12/17 Jan MMR
- 12/14/16 Dec MMR 11/29-30/16 JAXA TIM at Caltech
- 11/09/16 Nov MMR
- 09/27/16 RT validation test
- 09/14/16 Sept MMR
- 08/10/16 Aug MMR
- 07/26-28 POIME
- 07/13/16 July MMR 06/08/16 June MMR
- 05/11/16 May MMR
- 04/14/16 Post-CDR Briefing to DPMC
- 04/12/16 April MMR 03/29/16 Post CDR DMC
- 03/08-09 Project CDR
- 02/10/16 February MMR
- 02/11/16 SpaceX Interface Telecom
- 02/11/10 Space. 02/10/16 ISS Interface CDR 02/09/16 Phase II Safety Review
- 01/27/16 POIMS
- 01/26/16 Payload I&T and ATLO Peer Review
- 01/25/16 V&V Peer Review
- 01/20/16 Firmware Peer Review
- 01/13/16 January MMR
- 01/12/16 Fracture Control Board Poview 4
- 01/07/16 Padiometer Mechanical Peer Review
- 01/04/16 Phase II Safety Data Package due
- 12/17/15 Thermal Peer Review
- 12/16/15 Electronics Peer Review
- 12/15/15 Tolocom Poor Roview
- 12/14/15 Ontics Detector & Calibration Peer Review
- 12/14/15 Optics, Detector & Campration Feet Review 12/10/15 Accommodation Confirmation Briefing to DPMC
- 12/07/15 Fracture Control Board Review 3
- 12/07/15 FSW Peer Review
- 12/04/15 MOS. GDS. and SDS Peer Review
- 12/02/15 Radiometer I&T Peer Review
 12/02/15 Science Peer Review
- 11/18/15 Payload Enclosure Peer Review
- 11/16/15 Fracture Control Board review 2
- 11/11/15 November MMR

- 11/05/15 Science Team Meeting #2 10/29/15 Scan Mechanism Peer Review
- 10/23/15 KDP-C
- 10/20/15 Fracture Control Board review 1
- 10/14/15 October MMR
- 10/05/15 DMC
- 09/16/15 September MMR
- 09/12/15 August MMP
- 07/28/15 PDR
- 07/23/15 JAXA Face to Face meeting
- 07/14/15 Phase I Safety Review
- 07/01/15 Science Peer Review

- 06/23/15 ISS Interface PDR
- 06/19/15 Thermal Peer Review
- 06/18/15 Ontics and Detector Peer Review
- 06/16/15 Scan mechanism Peer Review
- 06/15/15 Padiameter structure Peer review
- 06/10/15 Electronics Peer Review
- 06/10/15 MOS/GDS and SDS Peer Review
- 06/05/15 FSW Poor Review
- 05/27/15 U.S.T and ATLO Poor Poviow
- 05/26/15 Firmware Peer Review
- 05/21/15 Motor Control Peer Review
- 05/21/15 WAP Downselect
- 05/20/15 Wi-Fi Tableton Review
- 05/06/15 Heat Exchanger Design Review 04/30/15 Cold Panel Peer-Review
- 04/16/15 Cryocooler thermal analysis Tableton
- 04/16/15 Signal Chain/Fley Peer Review
- 04/15/15 KDP-R
- 04/09/15 April MAMP
- 02/25/15 Wi Fi WG at ISC
- 03/24/15 Safety TIM/phase 0 at ISC
- 03/17/15 JAVA Briefing
- 03/11/15 March MMR
- 03/05/15 Inheritance Review
- 02/10/15 SPP/MDP
- 01/17/15 January William 01/12/15 Raseline Walkthrough
- 12/14/14 FCOSTRESS Science Team Meeting
- 12/10/14 December MMR
- 11/19/14 November MMR
- 11/06/14 ISS Kickoff Meeting
- 11/04/14 ESSP/SMD Meeting
- 10/01/14 Authority To Proceed (ATP)



Project Status Summary

I	echr	nical	Sc	hedu	ıle	Prog	gram	mat	ic	Res	our	ces
FEB	MAR	APR	FEB	MAR	APR	FEB	MAR	APR		JAN	FEB	MAR
Υ	Υ	Υ	Υ	Υ	Υ	G	G	G		Υ	Υ	G

Detailed Description: (for items identified as yellow or red)

Technical: Firmware on DPU-I/O has limited data band-width, data compression not implemented/working and data sent to GDS was not readable during thermal ambient test.


SpX changed the interface design to the Dragon Trunk from pFSE 1.0 to 2.0 design. Still evaluating the changes needed to random vibration testing MGSE.

Schedule: Cryocooler Multiplexer (CCM) would not switch from side-A to side-B of redundant cryocooler electronics. Request to change the delivery schedule submitted to ESSPO.

Mass




Updated as-build mass of MSU, CCM, PCE and Close-out Panel.



Power





FPIE power updated with measured power.



EM Cryocooler Installation







ECOSTRESS Electronics Development



- 1. Focal Plane Interface assembly
- 2. Cryocooler multiplexer assembly
- 3. Central electronics unit
- 4. WiFi electronics box assembly
- 5. Mass storage unit
- 6. Cryocooler electronics
- 7. Power condition
- 8. Radiometer Instrument
- 9. Nadir Panel
- 10. GSE Hot Plate



ECOSTRESS electronics ambient thermal cycling test configuration

JECOSTRESS



- Some facts and figures
 - Focused on water use and availability
 - Selected in EVI-2
 - Class D mission on ISS
 - Uses PHyTIR developed under ESTO IIP
 - Deliver in early 2017
 - Launch in mid 2018
 - Nominal mission lifetime 1 year



L1 Science Requirements and Margins

Parameter	Science Requirement (from PLRA)	Current Best Estimate @ 400 km	
Ground Sample Distance (m) Crosstrack x Downtrack at nadir	≤ 100 x ≤100	68.5 x 38.5	
Swath width (ISS nominal altitude range is 385 to 415 km)	≥ 360	402	
Wavelength range (μm)	8-12.5	8-12.5	
Number of bands	≥ 3	5 TIR + 1 SWIR	
Radiometric accuracy (K @300K)	≤ 1	0.5	
Radiometric precision (K @300K)	≤ 0.3	0.15-0.25	
Dynamic Range (K)	270-335	200-500	
Data collection	CONUS, twelve 1,000 x1,000km key climate biomes and twenty-five FLUXNET sites. On average 1 hour of science data per day.	1.5 hours per day of science data	



ECOSTRESS Science Data Products

Data Product	Description	Initial Availability to NASA DAAC	Median Latency in Product Availability to NASA DAAC after Initial Delivery	NASA DAAC Location
Level 0	Raw collected telemetry	6 months after IOC	12 weeks	LPDAAC
Level 1	Calibrated Geolocated Radiances	6 months after IOC	12 weeks	LPDAAC
Level 2	Surface temperature and emissivity	6 months after Level 1 data products are available	12 weeks	LPDAAC
Level 3	Evapotranspiration	2 months after Level 2 data products are available	12 weeks	LPDAAC
Level 4	Water use efficiency and evaporative stress index	2 months after Level 3 data products are available	12 weeks	LPDAAC




Calibration and Validation

- On-board blackbodies
- Vicarious calibration sites
- Validation sites (FLUXNET)

Lake Tahoe







Summary





- ECOSTRESS is possible because of the development of the PHyTIR instrument for HyspIRI-TIR supported by ESTO
- ECOSTRESS will address a subset of the science associated with HyspIRI
- The ECOSTRESS mission will help answer three key science questions:
 - How is the terrestrial biosphere responding to changes in water availability?
 - How do changes in diurnal vegetation water stress impact the global carbon cycle?
 - Can agricultural vulnerability be reduced through advanced monitoring of agricultural water consumptive use and improved drought estimation?
- ECOSTRESS has a clearly defined set of data products and mature algorithms
- Opportunity for combined HyspIRI-like datasets using the European EnMAP/PRISM and ECOSTRESS with GEDI for structure

ECOSTRESS will launch in 2018 and provide highest spatial resolution thermal infrared data ever from the International Space Station. HyspIRI is planned for the 2023+ timeframe unless the Decadal Survey increases the priority!!



Q1. How is the terrestrial biosphere responding to changes in water availability?






Uncertainty in our knowledge of carbon response is directly dependent on water response uncertainty and how plants use water under drying conditions.


Red areas ("hotspots") are where global models disagree on water use efficiency (WUE) based biome changes with climate change. ECOSTRESS will reduce this uncertainty with measurements for WUE (GPP/ET).



Q2. How do changes in diurnal vegetation water stress impact the global carbon cycle?



samples throughout the day over 1 year (at 50o latitude shown, for example).



ECOSTRESS's diurnal sampling measures the shape of the daily ET cycle. The afternoon decline in ET is related to water stress (clear day).

I: Xylem refilling after initial water release.


II: ET at maximum/potential rate in the morning.

III: Stomata shut down water flux in the afternoon.


IV: ET resumes at maximum/potential in early evening when demand is reduced

Q3. Can agricultural vulnerability be reduced through advanced monitoring of agricultural water consumptive use and improved drought estimation?







Probability of producing valid ET estimates when satellite revisit time is 16 days (lower-right inset) vs. 4 days




fine-scale landscape heterogeneity such as agricultural systems (top) and riparian corridors (bottom) similar to Landsat (left), whereas MODIS (right) does not.



ECOSTRESS's temporal resolution provides a *9-fold* decrease in ET error relative to Landsat.



HyTES Acquisition: July 9, 2014



<u>Irrigated July 7-8:</u>

Organic Tomato

→ Mean LST = 309 K

Conventional
Tomato

→ Mean LST = 306 K

Irrigated July 2-3:

Organic Corn

→ Mean LST = 304 K

Conventional Corn

→ Mean LST = 303 K



→ Mean LST = 301.5 K